

TECHNICAL SPECIFICATIONS

REFRIGERATION

Main compressor: R404A
Hopper Refrigeration: R134A
Ice cream outlet temp.: -6°C

ELECTRICAL

Single Phase 230 V, 50Hz

ADVANCED ELECTRONIC SYSTEM

Microprocessor controls automatically regulate refrigeration by monitoring the product temperature and viscosity to maintain consistent quality.



Mix Feed Pump for higher overrun



SALIENT FEATURES

- Both sides of the system are operated independent of each other
- Electronic control system ensures consistent product quality
- Feather-touch operating system with display
- Cone counter incorporated
- Night mode to preserve the mix in the hopper
- Hygienic design
- Energy Efficient
- User-friendly controls
- Excellent after-sale service



ISF Industries (Private) Limited

15B/1, SIDCO Industrial Estate,
Ambattur, Chennai 600 098, INDIA.
Phones : +91 44 26242907, 26524512, 26524513.
Fax : +91 44 26245024.
E-mail : md@isfindustries.com; sales@isfindustries.com

INDUSTRIAL STAINLESS STEEL FABRICATIONS (PRIVATE) LIMITED

79/12, New Nuge Road, Peliyagoda, SRI LANKA.
Phone : +94 11 5378081.
Fax : +94 11 5378080.
E-mail : saleslanka@isfindustries.com



isfindustries.com

ISF SOFTY VENDING MACHINES

ice creams cash profits real hard!!

ISF Softy Ice Cream Machines are of hygienic design, simple to operate, user-friendly and require minimum maintenance.

1T

SINGLE FLAVOUR, TABLE-TOP MODEL

Refrigeration System
Main compressor - 1 no. (3150 Btu/hr)

Hopper cooling compressor - 1 no. (420 Btu/hr)

1HP Beater motor - 1 no.



Model	Output (70ml cones/hr)	Storage Capacity	Weight (kg)		Dimensions (mm)		
			Nett	Gross	Length	Width	Height
1T	100	8 litres x 1	100	110	440	700	735
2T	210	12.5 litres x 2	150	170	550	650	960



2T

DOUBLE FLAVOUR, TABLE-TOP MODEL

Refrigeration System
Main compressor - 1 no. (3650 Btu/hr)

Hopper cooling compressor - 1 no. (420 Btu/hr)

2HP Beater motor - 1 no.



2FP

DOUBLE FLAVOUR, MOVABLE MODEL

Double flavour, movable model

Refrigeration System
Main compressor - 2 nos. (3600 Btu/hr)

Hopper cooling compressor - 1 no. (420 Btu/hr)

0.75HP Beater motor - 2 nos.

Model	Output (70 ml cones/hr)	Pump	Storage Capacity	Weight (kg)		Dimensions (mm)		
				Nett	Gross	Length	Width	Height
1FS	120	No	8 litres x 1	250	300	830	450	1410
1FP	150	Yes	8 litres x 1	260	310	830	450	1410
2FS	240	No	8 litres x 2	300	350	790	575	1410
2FP	300	Yes	8 litres x 2	320	370	790	575	1410